



# Material Safety Data Sheet

Version: 1.2  
06/07/2007

## SM2128 55G-Drum (450.0LBS-204.30KG) SILICONE EMULSION

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Manufactured By:** Waterford Plant  
260 Hudson River Rd  
Waterford NY 12188

**Revised:** 06/07/2007  
**Preparer:** PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS  
**CHEMTREC** 1-800-424-9300

**Chemical Family/Use:** Silicone emulsion  
**Formula:** Polydimethylsiloxane emulsion

#### HMIS

Flammability: 1      Reactivity: 0      Health: 0      Prot. Equipm.:

#### NFPA

Flammability: 1      Reactivity: 0      Health: 0      Special Haz.:

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<b><u>A. HAZARDOUS</u></b>		
Ethoxylated Nonylphenol	9016-45-9	1 - 5 %
<b><u>B. NON-HAZARDOUS</u></b>		
Water	7732-18-5	60 - 90 %
Polydimethylsiloxane	63148-62-9	30 - 60 %
Polyoxyethylene sorbitan mono-oleate	9005-65-6	1 - 5 %

### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Attention! This material is not considered hazardous by the OSHA Hazard Communication Standard 29 CFR 1910.1200

Form: Liquid

Color: white

Odor: odourless

#### POTENTIAL HEALTH EFFECTS

##### INGESTION

No adverse effects are expected under normal conditions of use.

**SM2128 55G-Drum (450.0LBS-204.30KG)  
SILICONE EMULSION**

---

**SKIN**

May cause mild skin irritation.

**INHALATION**

No adverse effects are expected under normal conditions of use.

**EYES**

May cause mild eye irritation.

**MEDICAL CONDITIONS AGGRAVATED**

None known.

**SUBCHRONIC (TARGET ORGAN )**

None known.

**CHRONIC EFFECTS / CARCINOGENICITY**

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

**ROUTES OF EXPOSURE**

Eyes; Absorption through skin.

**4. FIRST AID MEASURES**

**INGESTION**

Do NOT induce vomiting. If victim is conscious, give 2 glasses of water. Never give anything by mouth to an unconscious person. Obtain medical attention.

**SKIN**

Wash off with soap and water. Get medical attention if symptoms occur.

**INHALATION**

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

**EYES**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**NOTE TO PHYSICIAN**

Treatment is symptomatic and supportive.

**5. FIRE-FIGHTING MEASURES**

**FLASH POINT:**

215.50 °C; 420 °F

**METHOD:**

closed cup

**IGNITION TEMPERATURE:**

Not applicable

**SM2128 55G-Drum (450.0LBS-204.30KG)  
SILICONE EMULSION**

---

**FLAMMABLE LIMITS IN AIR - LOWER (%):** Not applicable  
**FLAMMABLE LIMITS IN AIR - UPPER (%):** Not applicable

**SENSITIVITY TO MECHANICAL IMPACT:** No

**SENSITIVITY TO STATIC DISCHARGE**  
Sensitivity to static discharge is not expected.

**EXTINGUISHING MEDIA**  
All standard extinguishing agents are suitable.

**SPECIAL FIRE FIGHTING PROCEDURES**  
Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**  
Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

## 7. HANDLING AND STORAGE

**STORAGE**  
Keep container closed. Recommended Storage Between 35F (2C) and 80F(26 C).

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**  
Avoid contact with eyes. Keep away from children. Do not freeze. Stir well before using. Attention: Not for injection into humans. May generate formaldehyde at temperatures greater than 150 C (300 F). See Section 10 of MSDS for details.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS**  
Eyewash stations; Showers; Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

**RESPIRATORY PROTECTION**  
If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29 CFR 1910.134).



**SM2128 55G-Drum (450.0LBS-204.30KG)  
SILICONE EMULSION**

**PROTECTIVE GLOVES**

Impermeable or chemical resistant gloves.

**EYE AND FACE PROTECTION**

Safety glasses with side-shields

**OTHER PROTECTIVE EQUIPMENT**

Wear suitable protective clothing and eye/face protection.

**Exposure Guidelines**

Component	CAS RN	Source	Value
-----------	--------	--------	-------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>BOILING POINT - C &amp; F:</b>	100.00 °C; 212 °F
<b>VAPOR PRESSURE (20 C) (MM HG):</b>	Same value as water
<b>VAPOR DENSITY (AIR=1):</b>	> 1
<b>FREEZING POINT:</b>	0.00 °C; 32 °F; Not applicable
<b>MELTING POINT:</b>	0.00 °C; 32 °F; Not applicable
<b>PHYSICAL STATE:</b>	Liquid
<b>ODOR:</b>	odourless
<b>COLOR:</b>	white
<b>EVAPORATION RATE (BUTYL ACETATE=1):</b>	< 1
<b>SPECIFIC GRAVITY (WATER=1):</b>	ca. 1.00
<b>DENSITY:</b>	ca. 0.9825 g/cm <sup>3</sup>
<b>ACID / ALKALINITY (MEQ/G):</b>	~7
<b>pH:</b>	ca. 7.5 - 9
<b>VOLATILE ORGANIC CONTENT (VOL):</b>	Not applicable
<b>SOLUBILITY IN WATER (20 C):</b>	Soluble
<b>SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):</b>	No data available
<b>VOC EXCL. H<sub>2</sub>O &amp; EXEMPTS (G/L):</b>	< 10

**10. STABILITY AND REACTIVITY**

**STABILITY**

Stable

**SM2128 55G-Drum (450.0LBS-204.30KG)  
SILICONE EMULSION**

---

**HAZARDOUS POLYMERIZATION**

Will not occur

**HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS**

After evaporation of water, residue can burn to produce:; Carbon dioxide (CO<sub>2</sub>); Carbon monoxide; Silicon dioxide.; formaldehyde; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

**CONDITIONS TO AVOID**

None known.

**11. TOXICOLOGICAL INFORMATION**

**ACUTE ORAL**

Remarks: No data available

**ACUTE DERMAL**

Remarks: No data available

**ACUTE INHALATION**

Remarks: No data available

**OTHER**

Product mixture tested. Not a primary eye or skin irritant. Not a skin sensitizer.

**SENSITIZATION**

Test Type: Sensitisation, skin; Result: Did not cause sensitization on laboratory animals.

**SKIN IRRITATION**

Species: rabbit; Result: No skin irritation

**EYE IRRITATION**

Species: rabbit ; Result: No eye irritation

**MUTAGENICITY**

No data available

**12. ECOLOGICAL INFORMATION**

**ECOTOXICOLOGY**

No data available

**SM2128 55G-Drum (450.0LBS-204.30KG)  
SILICONE EMULSION**

**CHEMICAL FATE**

No data available

**DISTRIBUTION**

No data available

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.

**14. TRANSPORT INFORMATION**

**Further Information:**

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

**15. REGULATORY INFORMATION**

**Inventories**

Canada DSL Inventory	y (Positive listing)
Japan Inventory of Existing & New Chemical Substances (ENCS)	y (Positive listing)
Korea Existing Chemicals Inventory (KECI)	y (Positive listing)
China Inventory of Existing Chemical Substances	y (Positive listing)
Australia Inventory of Chemical Substances (AICS)	y (Positive listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (Positive listing)
TSCA list	y (Positive listing)
EU list of existing chemical substances	y (Positive listing)
Canada NDSL Inventory	n (Negative listing)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

**US Regulatory Information**

**CERCLA**

**PRODUCT COMPOSITION**

**Chemical**

**CERCLA Reportable Quantity**





**SM2128 55G-Drum (450.0LBS-204.30KG)  
SILICONE EMULSION**

---

CLEAN AIR ACT

CLEAN WATER ACT

SARA SECTION 302

SARA (311,312) HAZARD CLASS  
No SARA Hazards

SARA (313) CHEMICALS  
75-21-8, Ethylene Oxide

**Canadian Regulatory Information**

WHMIS HAZARD CLASS  
NON-CONTROLLED

**Other**

SCHDLE B/HTSUS: 3910.00 Silicones in Primary Form

ECCN: EAR99

**CALIFORNIA PROPOSITION 65**

Warning! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.  
75-21-8, Ethylene Oxide.

**16. OTHER INFORMATION**

---

**OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. C = ceiling limit NEGL = negligible EST = estimated NF = none found  
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).