



# SAFETY DATA SHEET

## Polyflon PTFE M-15

### SECTION 1: CHEMICAL PRODUCT & COMPANY IDENTIFICATION

**DAIKIN TRADE NAME:** Polyflon PTFE M-15 Powder  
**FEATURE AND APPLICATION:** PTFE Packing, Gaskets, Chemical Linings, Valves, Sheets, etc.  
**CHEMICAL FAMILY:** Polytetrafluoroethylene (PTFE)  
**COMPANY:** Daikin America, Inc.  
20 Olympic Drive  
Orangeburg, New York 10962  
**EMERGENCY PHONE:** 1-256-306-5000  
**PRODUCT INFORMATION:** 1-800-365-9570 (9 am to 5 pm Eastern Standard Time)

### SECTION 2: HAZARD IDENTIFICATION

**GHS CLASSIFICATION:** Eye Irritation, Category 2B  
Mild Skin Irritation – Not Classified  
Acute Toxicity – Classification Not Possible  
Respiratory Sensitization – Classification Not Possible  
Skin Sensitization – Not Classified

**GHS LABEL REQUIREMENTS:** Symbol – None  
Signal Word - Warning  
Hazard Statement(s) – H320 - Causes eye irritation  
Precautionary Statement(s) - P264 – Wash hands thoroughly after handling  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 – If eye irritation persists: Get medical attention.

**OTHER HAZARDS:** The fluoropolymer contained in this product in its raw form is nearly inert. Processing above 350 °C, may produce hydrogen fluoride and other toxic fluorinated compounds. Inhalation of these compounds may result in serious lung irritation. Inhalation of vapors and fumes may cause flu-like symptoms (e.g., chills, fever, cough) that may not occur until several hours after exposure and typically pass within about 36 to 48 hours. Contact with molten material will cause burns.  
Excessive airborne concentrations of the powder may cause reduced visibility.

### SECTION 3: INFORMATION ON INGREDIENTS

COMPONENT	CAS NO.	Wt%
Polytetrafluoroethylene	9002-84-0	100

---

## SECTION 4. FIRST AID MEASURES

---

**INGESTION:** Consult a physician immediately.

**EYE CONTACT:** Flush with large amounts of water for 10-15 minutes. Consult a physician if needed.

**SKIN CONTACT:** Wash affected area with soap and water.

If you come in contact with molten material, do not attempt to remove it. Immediately flush affected area with cold water and cover with a clean dressing. Consult a physician to remove molten material.

**INHALATION:** Leave the contaminated area and seek fresh air. If breathing is difficult, contact a physician.

---

## SECTION 5. FIRE FIGHTING MEASURES

---

**EXTINGUISHING MEDIA:** Alcohol foam, CO<sub>2</sub>, dry chemical or water spray

**PROTECTIVE EQUIPMENT:** Use NIOSH/MSHA approved SCBA and bunker gear. Evolution of acidic gases may require complete wash down of protective clothing prior to removal.

**HAZARDOUS COMBUSTION PRODUCTS:** In case of fire or if processing at high temperatures, toxic gases including hydrofluoric acid, perfluoroisobutylene, and carbonyl fluoride may be formed.

**EXPLOSION:** PTFE is a non-combustible dust.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

---

Ensure cleanup is done only by trained personnel wearing appropriate personal protective equipment.

Collect spilled material in a container and seal.

Do not allow to enter sewer, surface or ground water.

Spilled material is a slipping hazard.

---

## SECTION 7. HANDLING & STORAGE

---

### HANDLING

Use product only for intended purpose.

Close containers after each use.

Wash hands after handling.

If smoking tobacco becomes contaminated by this material, exposure to toxic gases through inhalation can occur.

Therefore, do not smoke in the work areas and wash hands and face after handling in order to avoid transfer of material onto tobacco.

Do not allow material to be exposed to excessive heat (e. g., from use of torch, welding, etc).

Provide good room ventilation.

### STORAGE

Keep away from heat, steam or sunlight.

Store in a tightly closed container.

---

## SECTION 8. EXPOSURE CONTROLS & PERSONAL PROTECTIVE EQUIPMENT

---

### EXPOSURE LIMITS:

#### Particulates, not otherwise regulated

OSHA PEL: 15 mg/m<sup>3</sup>

ACGIH TLV: 10 mg/m<sup>3</sup>

NIOSH REL: 10 mg/m<sup>3</sup>

Excessive exposure to thermal degradation products could result in delayed pulmonary edema in some cases, and on very high exposure, damage to the liver and kidneys. These substances may include: perfluoroisobutylene (TLV = 10 ppb), carbonyl fluoride (TLV = 2 ppm TWA, 5 ppm STEL), hydrogen fluoride (TLV = 2 ppm Ceiling, 0.5 ppm TWA).

<b>RESPIRATORY PROTECTION:</b>	Normally not necessary. If material is heated above 350 °C, use a respirator for acidic gases. Respirator for nuisance dusts is required if airborne levels exceed the established Occupational Exposure Limits.
<b>EYE PROTECTION:</b>	Safety glasses with side shields or goggles
<b>PROTECTIVE CLOTHING:</b>	Appropriate gloves and clean room clothing.
<b>VENTILATION:</b>	Use local exhaust ventilation if material is heated above 350 °C or if spraying or coating.
<b>OTHER PROTECTIVE EQUIPMENT:</b>	Eyewash station and safety shower.

---

## SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

---

<b>APPEARANCE:</b>	Off white powder
<b>ODOR:</b>	None
<b>ODOR THRESHOLD:</b>	Not Applicable
<b>pH:</b>	Not Applicable
<b>MELTING POINT:</b>	332 ~ 352 °C
<b>BOILING POINT/RANGE:</b>	Not Applicable
<b>FLASH POINT:</b>	Non-flammable
<b>FLAMMABLE LIMITS:</b>	LEL – None UEL - None
<b>EVAPORATION RATE (Butyl acetate=1):</b>	Not Applicable
<b>VAPOR PRESSURE:</b>	Not Applicable
<b>VAPOR DENSITY:</b>	Not Applicable
<b>SPECIFIC GRAVITY (H<sub>2</sub>O=1):</b>	2.10 ~ 2.30 at approximately 25 °C
<b>APPARENT DENSITY:</b>	0.3 ~ 0.6 g/cm <sup>3</sup>
<b>SOLUBILITY(IES):</b>	Insoluble
<b>PARTITION COEFFICIENT (n-octanol/water):</b>	Not Available
<b>AUTO-IGNITION TEMPERATURE:</b>	Not Applicable
<b>DECOMPOSITION TEMPERATURE:</b>	377 °C (1 ppb TGA)
<b>VISCOSITY:</b>	Not Applicable
<b>AVERAGE PARTICLE SIZE:</b>	10 ~ 800 Microns (Generally 10 ~ 100 Microns)

---

## SECTION 10. STABILITY & REACTIVITY

---

<b>STABILITY:</b>	Stable
<b>CONDITIONS TO AVOID:</b>	Heat, sparks and open flame – material will decompose.
<b>INCOMPATIBILITIES:</b>	Molten alkali metals, interhalogen compounds, and some kinds of amines; finely divided metallic powder or filler. Small particles of fluoropolymer resins can become extremely combustible in the presence of various metal fines. Metal fines (e.g. aluminum and magnesium) mixed with powdered PTFE, when exposed to temperatures above 420 °C, may react violently producing fire and/or explosion.
<b>HAZARDOUS POLYMERIZATION:</b>	Should not occur
<b>HAZARDOUS DECOMPOSITION:</b>	Decomposition or by-products and toxic by-products including hydrofluoric acid, perfluoroisobutylene, and carbonyl fluoride may be formed at very high temperatures.

---

## SECTION 11. TOXICOLOGICAL INFORMATION

---

### ACUTE EFFECTS OF EXPOSURE

<b>Ingestion:</b>	Harmful if swallowed. Small amounts (tablespoonfuls) during normal handling are not likely to cause injury. Larger amounts may cause injury.
<b>Eye Contact:</b>	May cause eye irritation
<b>Skin Contact:</b>	May cause slight irritation
<b>Inhalation:</b>	When thermally decomposed, this material can cause polymer fume fever. Airborne concentrations of the powder in excess of Occupational Exposure Limits may cause irritation to the upper respiratory tract and may aggravate pre-existing respiratory conditions.

<b>CHRONIC EFFECTS OF EXPOSURE:</b>	No Data Available
<b>ACUTE TOXICITY:</b>	No Data Available
<b>SKIN CORROSION/IRRITATION:</b>	No Data Available
<b>SERIOUS EYE DAMAGE/IRRITATION:</b>	No Data Available
<b>RESPIRATORY OR SKIN SENSITIZATION:</b>	No Data Available
<b>GERM CELL MUTAGENICITY:</b>	No Data Available
<b>CARCINOGENICITY:</b>	None of the components in this material are listed by NTP, OSHA or IARC.
<b>REPRODUCTIVE TOXICITY:</b>	No Data Available
<b>STOT-SINGLE EXPOSURE:</b>	No Data Available
<b>STOT-REPEATED EXPOSURE:</b>	No Data Available
<b>ASPIRATION HAZARD:</b>	Not Applicable

---

## SECTION 12. ECOLOGICAL INFORMATION

---

<b>ECOTOXICITY:</b>	No data. Expected to be low due to the near-zero water solubility of the polymer. Material is considered inert and not expected to be biodegradable or toxic.
<b>ENVIRONMENTAL FATE:</b>	No data

---

## SECTION 13. DISPOSAL CONSIDERATIONS

---

Comply with Federal, State and Local regulations concerning health and environment when disposing of materials. Regulations may also apply to empty containers, liners, or rinsate. Usually considered an inert packaging material that can be recycled or landfilled. **DO NOT INCINERATE** unless incinerator is capable of scrubbing hydrogen fluoride and other acidic combustion products.

---

## SECTION 14. TRANSPORT INFORMATION

---

<b>UN CLASSIFICATION:</b>	Not applicable
<b>DOT HAZARD DESCRIPTION:</b>	Not applicable
<b>CANADIAN TRANSPORTATION OF DANGEROUS GOODS (TDG):</b>	Not applicable

---

## SECTION 15. REGULATORY INFORMATION

---

<b>TSCA:</b>	All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substance Control Act (TSCA) Chemical Substance Inventory.
<b>California Proposition 65:</b>	This product does not contain intentionally added (meaning deliberate use in the formulation of a product or subpart where its continued presence is desired to provide a specific characteristic, appearance or quality) materials which are listed on the California Proposition 65 list.
<b>REACH SVHC:</b>	This product does not contain intentionally added (meaning deliberate use in the formulation of a product or subpart where its continued presence is desired to provide a specific characteristic, appearance or quality) materials which are listed on the REACH Substances of Very High Concern (SVHC) list.
<b>RoHS:</b>	This product does not contain intentionally added lead, mercury, cadmium, PBB (polybrominated biphenyl) or PBDE (polybrominated diphenyl ether); unintentionally added (trace) amounts of lead, mercury, hexavalent chromium, PBB (polybrominated biphenyl), or PBDE (polybrominated diphenyl ether) in amounts greater than 1000 ppm (0.1% by weight) per homogenous material (substance or mixture of substances with uniform composition such as solders, resins, platings, etc.); cadmium in amounts greater than 75 ppm per homogenous material.
<b>Declaration on Allergens:</b>	Based upon the information provided by Daikin America Inc.'s suppliers, none of the constituent parts used by Daikin America Inc. in the manufacture of this product were made with peanuts, tree nuts, fish, shell fish, eggs, milk, wheat or soy (or any ingredients derived from these products).

- Animals or Animal bi-products:** Based on a comprehensive investigation, no animals or animal bi-products are used in the manufacturing process. Please note that we do not investigate the contents of peripherals and/or package accessories.
- Human or Human bi-products:** Based on a comprehensive investigation, no human or human bi-products are used in the manufacturing process. Please note that we do not investigate the contents of peripherals and/or package accessories.
- Absence of PFOA:** This product does not contain intentionally added PFOA (perfluorooctanoic acid).
- Other:** State and local regulations may have specific requirements for this product or components of this product; consult specific state and local regulatory requirements for additional information.

---

## **SECTION 16. OTHER INFORMATION**

---

For additional information, refer to the American Conference of Governmental Industrial Hygienists (ACGIH) documentation of TLV's (Threshold Limit Values) for individual components, Fluoropolymers Safe Handling Guide published by The Society of the Plastics Industry, and the DOT Emergency Response Guidebook.

Daikin America, Inc. (DAI) believes the information in this SDS to be correct as of the date issued, but DAI assumes no liability for the accuracy or completeness of the data relied on in preparing this SDS. DAI makes no warranties in this SDS, either express or implied, and excludes all warranties, including without limitation any implied warranty of merchantability, fitness for a particular purpose or course of performance, or usage of trade.

DAI may provide SDS information in electronic form as a customer service. Due to the remote possibility that electronic transfer may result in errors, omissions or alterations in this information, DAI makes no representation or warranty as to its completeness or accuracy when so transferred.

**SDS Issued: 10/17/2003**

**SDS Revised: 06/04/2013**