

# Flexsys America L.P.

Material Safety Data Sheet

Page 1 of 6

Draft Date: 2/11/00

MSDS Number: FLXP0094

CRYSTEX 60 OT 10

## Section 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product: **CRYSTEX 60 OT 10**  
MSDS Number: FLXP0094  
Chemical Name: Polymerized Sulfur with a naphthenic dedusting oil  
Synonyms: Insoluble Sulfur (oil-treated)

Supplying Company: Flexsys America L.P.  
260 Springside Drive  
Akron, Ohio 44333 USA

**EMERGENCY NUMBERS: CHEMTREC 800-424-9300 TOLL FREE [USA and TERRITORIES]  
703-527-3887 ELSEWHERE [COLLECT CALLS ACCEPTED]  
CANUTEC 613-996-6666 [Canada] SETIQ 91-800-00-214 [Mexico]**

## Section 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component:	CAS Number:	Usage Percentage:
Polymeric Sulfur *	9035-99-8	54%
Sulfur *	7704-34-9	36%
Naphthenic Oils	Various	10%

\*This material is identified as a hazardous chemical under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200)

## Section 3. HAZARDS IDENTIFICATION

### WARNING!

Emergency Overview: BURNING SULFUR EMITS HIGHLY TOXIC FUMES.  
DUST SUSPENDED IN AIR IGNITES EASILY.  
MAY CAUSE EYE IRRITATION.  
MAY CAUSE RESPIRATORY IRRITATION.

#### Potential Routes of Exposure:

Eye Contact: May cause eye discomfort and physical irritation.  
Skin Contact: Contact may cause mild skin irritation.  
Inhalation: Exposure to a high concentration of the dust may cause respiratory tract irritation, coughing, sneezing and tears.  
Ingestion: This material is considered practically non-toxic if swallowed.

MARKETED BY

**HARWICK STANDARD  
DISTRIBUTION CORPORATION**  
60 S. Seiberling Street • Akron, Ohio 44305

### Section 4. FIRST AID MEASURES

**IN EYES:** Flush eyes with large amounts of running water for at least 15 minutes, holding eyelids apart. Remove contact lenses. DO NOT RUB EYES! Do not neutralize with chemical agents. Do not use oils or ointments. Get medical attention if eye is irritated.

**ON SKIN:** Thoroughly wash all affected areas. Remove contaminated clothing and equipment. Launder any contaminated clothing and clean shoes before reuse. Get medical attention if irritation occurs.

**INHALED:** Remove to fresh air. In cases of respiratory problems, get medical attention. If victim is not breathing, give artificial respiration. If breathing is difficult, give oxygen, preferably under the direction of a physician.

**SWALLOWED:** If victim is conscious and alert, immediately give several glasses of water and induce vomiting. Keep victim's head below hips to avoid aspiration of vomitus. Give fluids until vomitus is clear. Get medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR CONVULSING PERSON. If the victim is unconscious,, monitor pulse, breathing and the airway. If breathing stops, begin artificial respiration. If the heart stops, begin cardiopulmonary resuscitation (CPR) and get immediate medical attention.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Persons with pre-existing lung disease may be at increased risk from inhalation.

**NOTE TO PHYSICIAN:** No specific antidote is known. Treat each patient symptomatically.

### Section 5. FIRE FIGHTING MEASURES

Yellow powder with a slight odor

Flash Point °F/°C: 405°F Sulfur / 207.22°C

Autoignition Temp °F/°C: 450°F Sulfur / 232.22°C

Flash Method: Closed Cup

Extinguishing Method: Water fog, foam, or carbon dioxide. Direct high pressure water stream could disperse dust clouds and cause an explosion.

Procedures and Equipment: As in any fire, prevent human exposures to fire, smoke, fumes or the products of combustion. Evacuate non-essential persons from the fire area. Firefighters and other emergency responders should wear full-face positive pressure demand self-contained breathing apparatus, impervious protective clothing and boots. If possible to do safely, remove containers from the fire area. HIGH-PRESSURE WATER MAY DISPERSE DUST CLOUDS IN AIR WHICH COULD CAUSE A DUST EXPLOSION. USE ONLY A FINE WATER FOG to extinguish fires involving this material. Wet down thoroughly to prevent reignition. Reignition can occur at temperatures above 428°F (220°C). Dike fire water for later disposal. Do not allow contaminated water to enter storm drains, watersheds or waterways. Thoroughly decontaminate all equipment after use.

Hazardous Products: Sulfur Dioxide Gas -- HIGHLY TOXIC -- Extreme exposures may cause pulmonary edema and death

Fire & Explosion Hazards: POSSIBLE DUST EXPLOSION. Sulfur dust is flammable and suspended dust will ignite easily and could explode, especially in confined areas. Eliminate sources of friction with dry powder to prevent static electricity in presence of flammables. (See NFPA-77, Chapter 6)

### Section 6. ACCIDENTAL RELEASE MEASURES

#### SPILL OR LEAK:

Wear dust-tight goggles, gloves, and use respiratory protection if ventilation is inadequate. Avoid breathing the dust of this material. Remove or turn off any ignition sources in the area.

Stop the source of the spill. Using a hand broom and non-sparking tools, sweep up spilled material being careful not to create dust. Vacuuming SHOULD NOT be used because of static electricity and sparking. Return sweepings to stock or, if contaminated, place into a clean, dry chemical waste container for disposal.

CERCLA REPORTABLE QUANTITY (RQ) : Not Applicable

### Section 7. HANDLING AND STORAGE

**Handling:** Keep away from all sources of heat, flame and sparks. Avoid creating dust clouds in handling, transfer and cleanup. Keep container closed when not in use. Wash thoroughly with soap and water after handling. This product is corrosive to copper and copper alloys. In the presence of water, sulfur will attack steel. Carbon steel and nickel alloys are the preferred materials for process equipment.

**Storage:** Store containers in a cool (below 30°C), dry, well-ventilated area. Store away from oxidizing agents, amines and strong bases. Avoid exposure to direct sunlight.

### Section 8. EXPOSURE CONTROL/PERSONAL PROTECTION

#### EYE PROTECTION:

Dust tight goggles are recommended when handling this material.

#### SKIN PROTECTION:

Wear chemical resistant gloves and clothing to prevent skin contact. Consult glove manufacturer for appropriate glove type. Wash contaminated skin promptly with plenty of soap and water. Launder contaminated clothing and clean protective equipment before reuse.

#### RESPIRATORY PROTECTION:

Avoid breathing the dust of this material. Use NIOSH/MSHA approved respiratory protection equipment when airborne exposure is excessive. Observe respirator use limitations specified by NIOSH/MSHA or the manufacturer. Respiratory protection programs must comply with 29 CFR 1910.134.

#### VENTILATION:

General plant ventilation should be adequate in most conditions. Avoid the accumulation and circulation of dust in the air. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

#### OTHER PROTECTION:

All food and smoking materials should be kept in a separate area away from the storage/use location. Eating, drinking, smoking and the application of cosmetics should be prohibited in areas where there is a potential for significant exposure to this material. Before eating, drinking, smoking or applying cosmetics, the hands, face and

# Flexsys America L.P.

## Material Safety Data Sheet

Page 4 of 6

Draft Date: 2/11/00

MSDS Number: FLXP0094

CRYSTEX 60 OT 10

exposed skin should be thoroughly washed.

### AIRBORNE EXPOSURE LIMITS

Product: Sulfur with naphthenic dedusting oil

OSHA PEL/8-hour TWA: 15 mg/m<sup>3</sup> (Total Dust)  
OSHA PEL/8-hour TWA: 5 mg/m<sup>3</sup> (Respirable Dust)  
ACGIH TLV/8-hour TWA: 10 mg/m<sup>3</sup>

Possible decomposition product: Sulfuric Acid

OSHA PEL/8-hour TWA: 1 mg/m<sup>3</sup>  
NIOSH REL/8-hour TWA: 1 mg/m<sup>3</sup>  
ACGIH TLV/8-hour TWA: 1 mg/m<sup>3</sup>  
ACGIH STEL 3 mg/m<sup>3</sup>

## Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow powder  
Odor: Slight odor  
Specific Gravity: 1.9 at 68°F (20°C)  
Water Solubility: Insoluble  
Other Solubility: Partially soluble in organic solvents  
Density: 350 mg/m<sup>3</sup> (Bulk)  
Note: Mean particle size: < 30 microns

## Section 10. STABILITY AND REACTIVITY

Stability: This material is stable at ambient temperatures and atmospheric pressures. It is not self reactive and is not sensitive to physical impact.

Materials to Avoid: Keep this material from contact with strong oxidizers, strong bases and amines.

Decomposition: Polymeric sulfur decomposes to rhombic sulfur if heated or on contact with strong bases or amines.

Hazardous polymerization: Not expected to occur.

## Section 11. TOXICOLOGICAL INFORMATION

Target Organs: Respiratory System, eyes, skin

Oral LD50 (rat):	>4000 mg/kg	Practically Non-Toxic
Dermal LD50 (rabbit):	>2000 mg/kg	Practically Non-Toxic
Eye Irritation (rabbit):		Moderately Irritating
Skin Irritation (rabbit):		Practically Non-Irritating

Skin: Single dose contact was non-irritating in animal tests. Prolonged or repeated skin contact may cause dermatitis and irritation. Sensitive individuals may have allergic reactions.

Eye: This material caused moderate irritation in animal tests.

# Flexsys America L.P.

## Material Safety Data Sheet

Page 5 of 6

Draft Date: 2/11/00

MSDS Number: FLXP0094

CRYSTEX 60 OT 10

Ingestion: Repeated ingestion may result in metabolic acidosis and production of hydrogen sulfide.

Inhalation: Prolonged or repeated inhalation may cause respiratory irritation, asthma and changes in pulmonary ventilation.

Carcinogenicity/mutagenicity: Not known

Reproductive Effects: Not known

Neurotoxicity: Not known

Other toxic effects: This material is classified as a nuisance dust.

### Section 12. ECOLOGICAL INFORMATION

Acute aquatic toxicity:

95Hr LC50 Bluegill:	>1000 mg/l	Practically Non-Toxic
95Hr LC50 Rainbow Trout:	>1000 mg/l	Practically non-Toxic
48Hr LC50 Daphnia magna:	>1000 mg/l	Practically Non-Toxic

### Section 13. DISPOSAL CONSIDERATIONS

When discarded, this material is not a hazardous waste as defined by the Resource Conservation and Recovery Act (RCRA), 40 CFR Part 261.

Material that can not be used or chemically reprocessed should be burned in an approved incinerator equipped with a scrubber and afterburner, or landfilled in a secure landfill in accordance with all applicable federal, state and local regulations.

Empty containers retain product residue. Clean containers before disposal in accordance with all applicable local, state and federal regulations.

### Section 14. TRANSPORT INFORMATION

Not regulated in transport.

Not controlled under TDG (Canada).

NOTE: Crystex mixtures containing at least 10% oil have very poor burning properties and self-extinguish shortly after ignition. As indicated in paragraph 5.3.1.3 of the IMDG Code, mixtures which no longer exhibit the characteristics of a hazard class of a component (sulfur) should be classified as "non-hazardous" in transport.

### Section 15. REGULATORY INFORMATION

Worldwide chemical inventories: ALL components of this mixture appear on the following:

- TSCA (USA)
- DSL (Canada)
- EINECS (European Economic Community)
- AICS (Australia)
- ECL (Korea)
- ENCS (Japan)

RCRA: Not Regulated

CERCLA: Not Applicable

DOT: Not Regulated - see Section 14

FDA: Not Regulated For Use in 21 CFR (due to naphthenic oil content)

# Flexsys America L.P.

## Material Safety Data Sheet

Page 6 of 6

Draft Date: 2/11/00

MSDS Number: FLXP0094

CRYSTEX 60 OT 10

### SARA Hazard Notifications

Hazard Categories under Title III Rules: Immediate

Title III Section 313 Toxic Chemicals: None

WHMIS Classification: Not Controlled

Component "Sulfur" appears on the following:

Massachusetts Substance List

New Jersey Right-To-Know Hazardous Substance

Pennsylvania Hazardous Substance List

Component "Naphthenic Oil" appears on the following:

Massachusetts Substance List

Naphthenic oils used in this product may consist of one or more of the following CAS#:

64742-52-5    64742-53-6    64742-65-0

Hazard Rating	Health	Flammability	Reactivity	Other
HMIS	1	1	0	N/A
NFPA	1	1	0	N/A

## Section 16. OTHER INFORMATION

Product use: Vulcanizing Agent

Last Revision: Add CANUTEC and SETIQ phone numbers (Section 1)

FOR NON-EMERGENCY INFORMATION: FLEXSYS AMERICAS PRODUCT SAFETY (330) 668-8281

Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof, Flexsys America L.P. makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Flexsys America be responsible for damages of any nature whatsoever resulting from the use of reliance upon information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.