

EXCEL POLYMERS LLC

MATERIAL SAFETY DATA SHEET



MASTERMIX TMTD 4187 SLAB-75

Version Number 1.3
Revision Date 07/16/2007

Page 1 of 8
Print Date 2/9/2010

1. PRODUCT AND COMPANY IDENTIFICATION

EXCEL POLYMERS LLC
14330 Kinsman Road, Burton, OH 44021

Telephone : Product Stewardship (440) 834-4644
Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Product name : MASTERMIX TMTD 4187 SLAB-75
Product code : AD0000064760
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	5 - 10
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	10 - 30
Tetramethyl thiuram disulfide (Thiram)	137-26-8	60 - 100

3. HAZARDS IDENTIFICATION

EM ERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Particulates, like other inert materials can be mechanically irritating.
Ingestion : May be harmful if swallowed.
Eyes : Particulates, like other inert materials can be mechanically irritating.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

EXCEL POLYMERS LLC

MATERIAL SAFETY DATA SHEET



MASTERMIX TMTD 4187 SLAB-75

Version Number 1.3
Revision Date 07/16/2007

Page 2 of 8
Print Date 2/9/2010

Medical Conditions : None known.
Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits
Upper explosion limit : Not applicable
Lower explosion limit : Not applicable

Autoignition temperature : Not applicable

Suitable extinguishing media : Water spray, Dry powder, Foam, Carbon dioxide (CO₂).

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

EXCEL POLYMERS LLC

MATERIAL SAFETY DATA SHEET



MASTERMIX TMTD 4187 SLAB-75

Version Number 1.3
Revision Date 07/16/2007

Page 3 of 8
Print Date 2/9/2010

- | | | |
|----------|---|---|
| Handling | : | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. |
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- | | | |
|--------------------------------|---|---|
| Respiratory protection | : | No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material. |
| Eye/Face Protection | : | Safety glasses with side-shields |
| Hand protection | : | Protective gloves |
| Skin and body protection | : | Long sleeved clothing |
| Additional Protective Measures | : | Safety shoes |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors. |

Exposure limit(s)

EXCEL POLYMERS LLC**MATERIAL SAFETY DATA SHEET****MASTERMIX TMTD 4187 SLAB-75**Version Number 1.3
Revision Date 07/16/2007Page 4 of 8
Print Date 2/9/2010

Components	Value	Exposure time	Exposure type	List:
Petroleum distillates, hydrotreated heavy naphthenic	500 ppm 2,000 mg/m3	PEL:		OSHA Z1
Petroleum distillates, hydrotreated light naphthenic	500 ppm 2,000 mg/m3	PEL:		OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Mist.	ACGIH
	10 mg/m3	Short Term Exposure Limit (STEL):	Mist.	ACGIH
Tetramethyl thiuram disulfide (Thiram)	1 mg/m3	Time Weighted Average (TWA):		ACGIH
	5 mg/m3	PEL:		OSHA Z1
	1 mg/m3	Time Weighted Average (TWA):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Solid	Evaporation rate	: Not applicable
Appearance	: pellets, Slabs, sheets	Specific Gravity	: Not determined
Color	: NO PIGMENT	Bulk density	: Not established
Odour	: Characteristic rubber odor	Vapour pressure	: Not applicable
Melting point/range	: Not determined	Vapour density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		

10. STABILITY AND REACTIVITY

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

EXCEL POLYMERS LLC**MATERIAL SAFETY DATA SHEET****MASTERMIX TMTD 4187 SLAB-75**

Version Number 1.3
 Revision Date 07/16/2007

Page 5 of 8
 Print Date 2/9/2010

CAS-No.	Chemical Name	Effect	Target Organ
64742-53-6	Petroleum distillates, hydrotreated light naphthenic	Irritant	Eyes, Skin.
64742-52-5	Petroleum distillates, hydrotreated heavy naphthenic	Irritant	Eyes, Skin.
137-26-8	Tetramethyl thiuram disulfide (Thiram)	Irritant	Eyes, Skin, Respiratory system.
		sensitizer	Eyes, Skin, Respiratory system.
		Systemic effects	Liver, Kidney, central nervous system (CNS).
		Toxic	Refer to LC50 / LD50 Data on MSDS..

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
137-26-8	Tetramethyl thiuram disulfide (Thiram)	LC50 Oral LD50	500 mg/m3 210 mg/kg	rat rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
64742-53-6	Petroleum distillates, hydrotreated light naphthenic	no	1	no
137-26-8	Tetramethyl thiuram disulfide (Thiram)	no	3	no

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.

EXCEL POLYMERS LLC

MATERIAL SAFETY DATA SHEET



MASTERMIX TMTD 4187 SLAB-75

Version Number 1.3
Revision Date 07/16/2007

Page 6 of 8
Print Date 2/9/2010

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.

Additional advice : Not applicable

13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification
Proper Shipping Name: Environmentally hazardous substances, solid, n.o.s.
Technical Name:
Hazard Class / Division 9
UN Number UN3077
Packing Group III
Label Required 9
Hazardous Substance Thiram
Reportable quantity: 13 LB

ICAO/IATA (air) Refer to specific regulation.

IMO / IMDG (maritime) Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component	RQ for Mixture/Product
---------------	---------	------------------	------------------------

EXCEL POLYMERS LLC
MATERIAL SAFETY DATA SHEET



MASTERMIX TMTD 4187 SLAB-75

Version Number 1.3
Revision Date 07/16/2007

Page 7 of 8
Print Date 2/9/2010

Tetramethyl thiuram disulfide (Thiram)	137-26-8	010 lbs	13 LB
--	----------	---------	-------

California Proposition 65 : Not applicable

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
THIRAM	137-26-8	60.00 - 100.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
137-26-8

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed

China IECS : Listed

Europe EINECS : Listed

Japan ENCS : Not determined

EXCEL POLYMERS LLC

MATERIAL SAFETY DATA SHEET



MASTERMIX TMTD 4187 SLAB-75

Version Number 1.3
Revision Date 07/16/2007

Page 8 of 8
Print Date 2/9/2010

Korea KECI : Listed

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.