

ADVASTAB® TM-3412

High Efficiency Methyltin Heat Stabilizer

DESCRIPTION

ADVASTAB® TM-3412 is formulated for use in substrate compounds or pipe compounds requiring increased stabilizer efficacy. The methyltin mercaptoester chemistry employed imparts excellent color hold at low cost for these applications.

GENERAL CHARACTERISTICS

Properties	Typical Values
Specific Gravity, g/cc (@25°C)	1.04
Weight, lb/gal (@25°C)	8.7
Viscosity, cps (@25°C)	60
Acid Value	3.0 (max.)
% Tin	9.2
% Mercaptan Sulfur	12.0
Color (Gardner)	9 (max.)

APPLICATIONS & RECOMMENDATIONS

Specifically optimized state-of-the-art reverse ester chemistry with optimized methyltin chemistry:

1. Highly efficient, excellent color stability, highest output, for any rigid Vinyl extrusion application
2. For single and multi-screw extrusions of potable water, DWV, sewer, electrical conduit and irrigation pipes
3. Fully approved uses in potable water pressure pipes under the PPI-PVC Generic Range Formulation
4. Outstanding color stability in many rigid Vinyl extrusions such as rigid interior profiles
5. Excellent long term stability performance in extrusions with long extruder dwell times
6. Fully compatible with nearly all of the commonly used processing aids and acrylic and ABS impact modifiers

PACKAGING

Available in Totes or Intermediate Bulk Container (IBC).

In US

Customer Service
1.855.638.2549
Fax 1.855.289.2885

In Europe

Customer Service
33(0)3.91.83.71.56
Fax 33(0)3.91.83.71.91

www.pmc-group.com

The information contained in this Technical Data Sheet (TDS) relates to specific products of PMC Organometallics, Inc. (Seller) and is based upon information available as of the date hereof. While the information herein is believed to be reliable, we do not guarantee its accuracy and a purchaser must make its own determination of a product's suitability for purchaser's use, for the protection of the environment, and for the health and safety of its employees and the purchasers of its products. Additional information relating to the products can be obtained from the applicable Safety Data Sheets (SDS) which are available upon request. Nothing in this TDS or any SDS shall be construed to modify, limit or preclude the operation and effect of any and all provisions of any applicable written sales contract and/or Seller's General Terms and Conditions of Sale under which the Products described in this TDS are sold and the provisions of such sales contract and/or Seller's General Terms and Conditions of Sale shall control. Seller's General Terms and Conditions of Sale are available for review upon request or at http://pmc-group.com/wp-content/uploads/2017/01/PMC_Group_General_Terms_and_Conditions_of_Sale.pdf. NOTHING IN THIS TDS SHALL CONSTITUTE A WARRANTY OR CERTIFICATION, EXPRESSED OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, QUALITY, USE, SAFETY OR FITNESS FOR ANY PARTICULAR PURPOSE. Nothing contained herein shall be construed as permission or a recommendation to practice any invention covered by a patent or other intellectual property without the permission of the owner thereof. Neither Seller nor any of its affiliates shall be responsible for the use of this information, or of any product, method, formulation, or apparatus described in this TDS.

ADVALUBE®, ADVAPAK®, ADVASTAB®, ADVAWAX®, Baion®, CrystalWax®, Kemamide®, Kemester® and Thermolite® are registered trademarks of PMC Group, Inc.

ADVASTAB® TM-3412

High Efficiency Methyltin Heat Stabilizer

TYPICAL APPLICATION FORMULATIONS

ADVASTAB® TM-3412 stabilizer is a very high performance thermal stabilizer developed especially for the most demanding pipe extrusions. The high performance is demonstrated by providing brilliant white color stability and long running times at the highest output rates at low loading levels. **ADVASTAB® TM-3412** stabilizer has proven itself over and over again to manufacture every size of Vinyl from 1/2 inch to 36 inch pressure pipes. The following table shows some starting point formulations that exemplify the variety of pipe applications where **ADVASTAB® TM-3412** stabilizer is commonly used.

	Pressure DWV			
	D-2241 D-1785 D-2665	Sewer D-3034 F-789	Duct F-512	Foam "Skins" F-891
Vinyl Resin (K=66)	100.0	100.0	100.0	100.0
TiO ₂ 0.5-1.0	0.5-1.0	0.5-1.0	0.5-1.0	0.75-1.0
CaCO ₃ Filler	3.0-5.0	15-30	2.0-4.0	3.0-5.0
PMC Biogenix Calcium Stearate	0.6	0.6	0.8	0.6
CrystalWax® 2054 (165°F)	1.2	1.2	1.2	1.2
Oxidized Polyethylene	0.15	0.20	0.15	0.15
Impact Modifier	—	—	2.0-5.0	0-3.0
ADVASTAB® TM-3412	0.30-0.35	0.30-0.35	0.35-0.45	0.3-0.4

SAFETY & HANDLING

ADVASTAB® TM-3412 stabilizer may be handled with the same normal precautions as other methyltin mercaptide stabilizers and organic liquids. In case of contact with skin, thoroughly wash with soap and water. In case of contact with eyes, flush with water and get medical attention immediately. Use with adequate ventilation and avoid excessive or prolonged exposure to the vapors.

We recommend that the material is stored in a cool, dry environment in a tightly closed container and used within 6 months after delivery. Iron or non-stainless steel should be avoided for piping, valves, and pumps. Teflon® gaskets are recommended. No part of the stabilizer handling system wetted by liquid should contain copper.



In US
Customer Service
1.855.638.2549
Fax 1.855.289.2885

In Europe
Customer Service
33(0)3.91.83.71.56
Fax 33(0)3.91.83.71.91

www.pmc-group.com

The information contained in this Technical Data Sheet (TDS) relates to specific products of PMC Organometallics, Inc. (Seller) and is based upon information available as of the date hereof. While the information herein is believed to be reliable, we do not guarantee its accuracy and a purchaser must make its own determination of a product's suitability for purchaser's use, for the protection of the environment, and for the health and safety of its employees and the purchasers of its products. Additional information relating to the products can be obtained from the applicable Safety Data Sheets (SDS) which are available upon request. Nothing in this TDS or any SDS shall be construed to modify, limit or preclude the operation and effect of any and all provisions of any applicable written sales contract and/or Seller's General Terms and Conditions of Sale under which the Products described in this TDS are sold and the provisions of such sales contract and/or Seller's General Terms and Conditions of Sale shall control. Seller's General Terms and Conditions of Sale are available for review upon request or at http://pmc-group.com/wp-content/uploads/2017/01/PMC_Group_General_Terms_and_Conditions_of_Sale.pdf. NOTHING IN THIS TDS SHALL CONSTITUTE A WARRANTY OR CERTIFICATION, EXPRESSED OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, QUALITY, USE, SAFETY OR FITNESS FOR ANY PARTICULAR PURPOSE. Nothing contained herein shall be construed as permission or a recommendation to practice any invention covered by a patent or other intellectual property without the permission of the owner thereof. Neither Seller nor any of its affiliates shall be responsible for the use of this information, or of any product, method, formulation, or apparatus described in this TDS.

ADVALUBE®, ADVAPAK®, ADVASTAB®, ADVAWAX®, Baion®, CrystalWax®, Kemamide®, Kemester® and Thermolite® are registered trademarks of PMC Group, Inc.

ENVIRONMENTAL AND SAFETY INFORMATION

BEFORE HANDLING THIS MATERIAL, READ AND UNDERSTAND THE MSDS (MATERIAL SAFETY DATA SHEET) FOR ADDITIONAL INFORMATION ON PERSONAL PROTECTIVE EQUIPMENT AND FOR SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION. For Environmental, Safety & Toxicology information, contact our Customer Service Department at 1-855-638-2549 (1-855-METALIX) to request a Material Safety Data Sheet.

MORE TECHNICAL INFORMATION AVAILABLE

Ask your PMC account manager for further information about other high quality PMC plastics additives for use in PVC resins, PVC alloys and other polymer systems. PMC offers its **Center for Vinyl Innovation (CVI)** where our field experienced technical staff maintains a full array of PVC testing capabilities to assist vinyl processors solve a range of formulation and processing problems. Set up a visit to the CVI to learn more about how PMC's technologists can help improve your vinyl processing applications.

PMC ORGANOMETALLIX THERMOLITE® AND ADVASTAB® HEAT STABILIZERS

PMC Organometallix offers a full range of Methyltin, Butyltin and Octyltin heat stabilizers. Our **Thermolite®** and **ADVASTAB®** heat stabilizers are designed for use in the production of rigid, semi-rigid and cellular PVC products. Organometallix has developed PVC heat stabilizers specifically for extruded siding, profiles and pipe, injection molding, blow molded bottles and calendered or extruded sheet. Organometallix offers a full line of stabilizers that meet FDA requirements for food contact grade PVC packaging as well as a full line of NSF authorized stabilizers for PVC potable water pipe & fittings.

PMC BIOGENIX ADVAPAK®, ADVALUBE®, ADVAWAX®, KEMAMIDE® AND KEMESTER® LUBRICANTS

PMC Biogenix offers a wide range of metallic stearates, specialty lubricants and other additives designed for all grades of polymer processing, including PVC pipe and profile extrusions, compounding, film and sheet and injection-molding applications. Biogenix brands are widely recognized. **ADVAWAX®** synthetic waxes are used in bottles, films and cellular PVC profile extrusions. **ADVALUBE®** specialty ester-based internal and external lubricants are designed for rigid PVC profile extrusion, calendered film and sheet, and blow molding applications. **ADVAPAK®** is family of multi-functional one-pack systems (OPS) combining heat stabilizer and lubricant technology designed for efficient extrusion of all types of PVC pipe and moldings. **Kemamide®** synthetic waxes find uses as slip agents and anti-block additives that provide excellent bloom control and secondary mold-release in polyolefins and engineering polymers such as nylon, PS and ABS. **Kemester®** lubricants are a range of glycerol esters and specialty esters that function as boundary lubricants, mold-release agents, emulsifiers, anti-stats, anti-fogs, and emollients in automotive plastics, etc.

PMC CRYSTAL BAION® AND CRYSTALWAX® LUBRICANTS

PMC Crystal manufactures **Baion®** and **CrystalWax®**, a broad range of standard paraffin and polyethylene wax blends along with options of including specialty lubricants produced by PMC Biogenix. Crystal lubricants are also available in custom formulations to meet specific customer requirements. Several **Baion®** products are fully authorized by NSF for use in PVC potable water systems. **Baion®** and **CrystalWax®** products find uses in PVC siding, window profiles, fencing, decking and trim applications to highlight a few.



In US
Customer Service
1.855.638.2549
Fax 1.855.289.2885

In Europe
Customer Service
33(0)3.91.83.71.56
Fax 33(0)3.91.83.71.91

www.pmc-group.com

The information contained in this Technical Data Sheet (TDS) relates to specific products of PMC Organometallix, Inc. (Seller) and is based upon information available as of the date hereof. While the information herein is believed to be reliable, we do not guarantee its accuracy and a purchaser must make its own determination of a product's suitability for purchaser's use, for the protection of the environment, and for the health and safety of its employees and the purchasers of its products. Additional information relating to the products can be obtained from the applicable Safety Data Sheets (SDS) which are available upon request. Nothing in this TDS or any SDS shall be construed to modify, limit or preclude the operation and effect of any and all provisions of any applicable written sales contract and/or Seller's General Terms and Conditions of Sale under which the Products described in this TDS are sold and the provisions of such sales contract and/or Seller's General Terms and Conditions of Sale shall control. Seller's General Terms and Conditions of Sale are available for review upon request or at http://pmc-group.com/wp-content/uploads/2017/01/PMC_Group_General_Terms_and_Conditions_of_Sale.pdf. NOTHING IN THIS TDS SHALL CONSTITUTE A WARRANTY OR CERTIFICATION, EXPRESSED OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, QUALITY, USE, SAFETY OR FITNESS FOR ANY PARTICULAR PURPOSE. Nothing contained herein shall be construed as permission or a recommendation to practice any invention covered by a patent or other intellectual property without the permission of the owner thereof. Neither Seller nor any of its affiliates shall be responsible for the use of this information, or of any product, method, formulation, or apparatus described in this TDS.

ADVALUBE®, ADVAPAK®, ADVASTAB®, ADVAWAX®, Baion®, CrystalWax®, Kemamide®, Kemester® and Thermolite® are registered trademarks of PMC Group, Inc.