



NATROCHEM, INC.
P.O. BOX 1205
SAVANNAH, GA 31402
(912) 236-4464 FAX: (912) 236-1919
www.natrochem.com

DATA SHEET
Natro-Cel 500N-A

Natro-Cel 500N-A is a blend of naphthenic process oil and silicon dioxide. It is compatible with synthetic elastomers and their additives. Made with high VGC / low aniline point oil, it blends easily and has good color stability.

Natro-Cel 500N-A exhibits the balance of properties that make it the preferred choice for non-rubber applications. For example, resin extending, PVC, textiles, caulking compounds and other applications.

TEST	TEST METHOD SPECIFICATION	
Actives Content, %	QCL-8.2.4-2-1	70 - 74
Carrier Content, %	QCL-8.2.4-2-1	26 - 30
Appearance	Visual	White to light tan powder

TYPICAL PROPERTIES

Actives Content, %	72
Carrier Content, %	28
Specific Gravity (Apparent)	1.107
Packaging	40# Net, Multi-wall Bags 1,000# Net, Supersack FIBC
Color	Off-White

Date of Revision: 2015-08-19

The information in this data sheet is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of these data or the use of this product, nor are any statements in this bulletin intended as recommendations to use our products in the infringement of any patents.

OTHER NATROCHEM PRODUCTS

**DLC® - Natro-Rez™ - Rosin Pitches - Tarene™
Natro-Flex™ - Tar-Cel™ - Natro-Cel™**