



TECHNICAL DATA SHEET

Neville Chemical Company
2800 Neville Road
Pittsburgh, PA 15225-1496

Phone: 412-777-4210
E-Mail: support@nevchem.com
Internet: www.nevchem.com

NEVCHEM® 140

PRODUCT DESCRIPTION

NEVCHEM® 140 is a thermoplastic low molecular weight, C9 hydrocarbon resin produced by catalytic polymerization of mixed aromatic and alicyclic monomers derived from petroleum feedstocks.

APPLICATIONS / END USES

- Sealants
- Construction Adhesives
- High Solids Solvent-Borne and Alkyd Based Coatings
- Asphalt Modification
- Litho Printing Inks

ATTRIBUTES / BENEFITS

- Compatible with Medium and Long Oil Alkyds
- Enhanced Wetting of Pigments and Fillers
- Improved Resistance to Acids and Alkalis
- Provides Excellent Leafting Characteristics for Metallic Pigments
- Improves Scorch Time
- Hydrophobic-Improved Moisture Resistance
- Soluble in Aliphatic Solvents and Oils
- Good Thermal Stability
- Low Molecular Weight
- Low VOC
- Low Odor

PROPERTIES

Property	Test Method	Typical Value	Specifications
Softening Point, R&B °C	ASTM E28	140	140 ± 5
Gardner Color (50% in 100 Solvent)	ASTM D1544	12.5	14 max.
Specific Gravity @ 25°C	ASTM D71	1.08	NA
Brookfield Viscosity, cp @ 180°C @ 200°C	ASTM 3236	8,375 1,575	NA
Molecular Weight Mn Mw	ASTM D5296	650 2,150	NA
Appearance	Visual	Amber	N/A

PACKAGING

NEVCHEM® 140 Resin is shipped in 50 lb. (22.7 kg.) bags or super sacks.

Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.

Revised: November 19, 2019