



# TECHNICAL DATA SHEET

Neville Chemical Company  
2800 Neville Road  
Pittsburgh, PA 15225-1496

Phone: 412-777-4210  
E-Mail: support@nevchem.com  
Internet: www.nevchem.com

# NP-10

## PRODUCT DESCRIPTION

NP-10 resin is a low molecular weight, liquid C9 tackifying hydrocarbon resin produced by catalytic polymerization of mixed aromatic and alicyclic monomers derived from petroleum feedstocks.

## APPLICATIONS / END USES

- Roofing Applications
- Specialty Tack Cloths
- Waterproofing
- SBR-Based Mastic Adhesives
- Rubber Compounding
- High Solids Alkyd-Based Coatings
- Litho Ink Pigment Dispersions

## ATTRIBUTES / BENEFITS

- Enhances Pigment Wetting and Dispersions
- Induces Flow and Levelling
- Tackifies and Plasticizes

## PROPERTIES

Property	Test Method	Typical Value	Specifications
Softening Point, R&B °C	ASTM E28	11	10 ± 5
Gardner Color (50% in 100 Solvent)	ASTM D1544	11.5	16 Max.
Specific Gravity @ 25°C	ASTM D71	1.0	N/A
Brookfield Viscosity @ 120°F, cps	ASTM 3236	2,100	N/A
Flash Point, °F (COC)	ASTM D92	400 Min.	N/A
Appearance		Viscous Amber Liquid	

**PACKAGING:** NP-10 Resin is shipped in 410 lb. net weight drums or bulk.

**TSCA Status:** Neville Chemical Company certifies that all components of this product are on the TSCA Inventory.

Revised: November 19, 2019