



HARWICK

S T A N D A R D

ISO 9001-2015 REGISTERED

Technical Data Sheet

Stan-Flux LV-1

Stan-Flux LV-1 is a medium viscosity aromatic process oil that is typically used in polar elastomers as a process aid.

TYPICAL PROPERTIES

Viscosity SUS at 100 °F, secs.	250
Specific gravity at 75 °F	0.99
Aniline Point, °C	45.0

08/06/2019 Revised 03/17/2020

HARWICK STANDARD MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE GOODS OR USES OF THE GOODS OR PERFORMANCE OF THE GOODS AND MAKES NO WARRANTIES OF THE FITNESS FOR PARTICULAR PURPOSE OR MERCHANTABILITY. BUYER ACKNOWLEDGES THAT HARWICK STANDARD WILL NOT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, DIRECT, OR SPECIAL DAMAGES ARISING, DIRECTLY, OR INDIRECTLY, IN RESPECT TO SUCH GOODS OR THE USE OR FAILURE THEREOF, WHETHER BASED ON BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE.

HARWICK STANDARD DISTRIBUTION CORPORATION

60 S. SEIBERLING ST. • P.O. Box 9360 • AKRON, OH 44305-0360 • U.S.A.

PHONE: (330) 798-9300 • FAX: (330) 798-0214

www.harwick.com