

Synpro® CALCIUM STEARATE 15F

Product Description

Synpro® CALCIUM STEARATE 15F is a high ash, free flowing granular (non-dusting) multifunctional (external / internal) lubricant and fusion promoter for rigid PVC pipe, siding, decking, profile extrusions, and Phenolics. Due to its optimum over-based properties, reduced die plate-out can be anticipated.

Through controlled engineering and chemical processes Synpro® CALCIUM STEARATE 15F can be readily airveyed, virtually eliminating dusting problems to the Operator and surrounding environment. Its dense flow-able properties enable optimum processing with automated weigh systems and dispersion mixing.

Synpro® CALCIUM STEARATE 15F is listed in NSF / ANSI International Standard 14-Plastics Piping System Components and Related Materials. Additionally it is suitable for use in food packaging applications in accordance with many FDA Code of Regulations; an updated complete list is available upon request.

Safety and Handling

Complete toxicity and handling information can be found on the Material Safety Data Sheet (MSDS), which is available upon request.

Typical Properties

Appearance	White free-flowing granular
Ash (CaO)	11.4%
Free Fatty Acid	0.3%
Moisture	3.4%
Melting Point	155°C
Apparent Density	0.7 g/cc
Fineness (Sieve)	≤ 15% through 200 Mesh

