




Product Literature

ISO 9001:2008 REGISTERED

VULCANIZING AGENT IS-HS-7020

Chemical Name: Insoluble Sulfur

Structure



Molecular Weight:

Class: Sulfur

CAS#: 9035-99-8

Vulcanizing Agent IS-HS-7020 is an oil treated, heat stable, polymeric sulfur.

Insoluble Sulfur is typically used with NR, IR, SBR, NBR, and EPDM.

Vulcanizing Agent IS-HS-7020 has typical properties of: Specific Gravity @ 1.58; Melt Point @ 101°C, and is available in a yellow oil treated powder.

12/23/14

HARWICK STANDARD MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE GOODS OR USES OF THE GOODS OR PERFORMANCE OF THE GOODS AND MAKES NO WARRANTIES OF THE FITNESS FOR PARTICULAR PURPOSE OR MERCHANTABILITY. BUYER ACKNOWLEDGES THAT HARWICK STANDARD WILL NOT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, DIRECT OR SPECIAL DAMAGES ARISING, DIRECTLY OR INDIRECTLY, IN RESPECT TO SUCH GOODS OR THE USE OR FAILURE THEREOF, WHETHER BASED ON BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE.

HARWICK STANDARD DISTRIBUTION CORPORATION

60 S. SEIBERLING ST. • P.O. BOX 9360 • AKRON, OH 44305-0360 • U.S.A.
PHONE: (330) 798-9300 • FAX: (330) 798-0214
WWW.HARWICKSTANDARD.COM